

Controls

Section	Page No.
Thermostatic Mixing Valves (TMVs)	
15mm TMV2 / 3 Thermostatic Mixing Valve	81
22mm TMV2 / 3 Thermostatic Mixing Valve	81
15mm TMV2 / 3 Thermostatic Mixing Valve (Isolators)	81
22mm TMV2 / 3 Thermostatic Mixing Valve (Isolators)	81

Thermostatic Radiator Valves (TRVs)	
Modern Thermostatic Radiator Valves	82
15mm Thermostatic Radiator Valves	82
15mm Pipe Connection Tubes	82
Angled Valves	83
Straight Valves	83
One Piece Reducing Bullet	83

Designer Radiator Valves	
Contemporary / Traditional Radiator Valves	84
Coloured Valves	84
Elements	84

Manual Radiator Valves	
Angled Manual Radiator Valves	85
Straight Manual Radiator Valves	85
Ancillaries	85

Our frequently ordered Controls products...



15mm Angled TRV (Twin Pack)
Page 83



Matt Black 15mm Angled TRV
Page 82



Brushed Brass 15mm Angled TRV
Page 82



Polished Chrome 15mm Angled TRV
Page 82



Polished Chrome Modern 15mm Valve
Page 84



Chrome 15mm Pipe Connection Tubes
Page 82

Control Features



Temperature Adjustment



Max Flow Temperature



Min. Operating Pressure



Max. Operating Pressure



Anti Scald

Guarantees

1 Years on Thermostatic Mixing Valves (TMVs)

Thermostatic Mixing Valves (TMVs)



15mm TMV2 / 3 Thermostatic Mixing Valve

Finish – Chrome
Dimensions – 98(h) x 140(w) mm



40015CBA



22mm TMV2 / 3 Thermostatic Mixing Valve

Finish – Chrome
Dimensions – 98(h) x 146(w) mm



40022CBA



15mm TMV2 / 3 Thermostatic Mixing Valve (Isolators)

Finish – Chrome
Dimensions – 98(h) x 132(w) mm



400MX15CBA



22mm TMV2 / 3 Thermostatic Mixing Valve (Isolators)

Finish – Chrome
Dimensions – 98(h) x 132(w) mm



400MX22CBA

Thermostatic Radiator Valves (TRVs)

Guarantees

1 Year on Thermostatic Radiator Valves (TRVs)

Modern Thermostatic Radiator Valves (TRVs)



Chrome (1/2" x 15mm)

Dimensions –
136(h) x 68(w) x 40(d) mm (Angled)
84(h) x 118(w) x 40(d) mm (Straight)
78(h) x 115(w) x 65(d) mm (Corner)

INCNT004AP-CP	Angled Valve
INCNT004ST-CP	Straight Valve
INCNT024	Corner Valve



Matt Black (1/2" x 15mm)

Dimensions –
136(h) x 68(w) x 40(d) mm (Angled)
84(h) x 118(w) x 40(d) mm (Straight)
78(h) x 115(w) x 65(d) mm (Corner)

INCNT004AP-BL	Angled Valve
INCNT004ST-BL	Straight Valve
INCNT024-BL	Corner Valve



Anthracite (1/2" x 15mm)

Dimensions –
136(h) x 68(w) x 40(d) mm (Angled)
84(h) x 118(w) x 40(d) mm (Straight)
78(h) x 115(w) x 65(d) mm (Corner)

INCNT004AP-AT	Angled Valve
INCNT004ST-AT	Straight Valve
INCNT024-AT	Corner Valve

15mm Thermostatic Radiator Valves (TRVs)



Chrome (Twin Pack)

Dimensions –
130(h) x 42(w) x 65(d) mm (Angled)
120(h) x 47(w) x 86(d) mm (Straight)

15PACKACP.1	Angled Valve
15PACKSCP.1	Straight Valve



Classic Polished Chrome (Twin Pack)

Dimensions –
139(h) x 56(w) x 55(d) mm

INST-AL055LC	Angled Valve
---------------------	--------------



Brushed Brass (1/2" x 15mm)

Dimensions –
136(h) x 68(w) x 40(d) mm

INCNT004AP-ZBBS	Angled Valve
------------------------	--------------

15mm Pipe Connection Tubes (Pair)



Chrome

Dimensions –
150(h) x 15(w) x 15(d) mm

INCNT005-C



Matt Black

Dimensions –
150(h) x 15(w) x 15(d) mm

INCNT005-MB



Anthracite

Dimensions –
150(h) x 15(w) x 15(d) mm

INCNT005-AT



Gloss White

Dimensions –
150(h) x 15(w) x 15(d) mm

INCNT005-GW

Guarantees

1 Year on Thermostatic Radiator Valves (TRVs)

Thermostatic Radiator Valves (TRVs)

Angled (TRVs)		Straight (TRVs)	
 <p>Best Seller</p> <p>White (15mm - Twin Pack)</p> <p>Dimensions – 140(h) x 76(w) x 48(d) mm</p> <p>Max 110°C Max 10 Bar</p> <p>15PACKAWHCP.1 Angled Valve</p>	 <p>White (10mm - Twin Pack)</p> <p>Dimensions – 140(h) x 76(w) x 48(d) mm</p> <p>Max 110°C Max 10 Bar</p> <p>10PACKAWHCP Angled Valve</p>	 <p>White (15mm - Twin Pack)</p> <p>Dimensions – 124(h) x 85(w) x 48(d) mm</p> <p>Max 110°C Max 10 Bar</p> <p>15PACKSWHCP.1 Straight Valve</p>	
 <p>White (15mm)</p> <p>Dimensions – 140(h) x 76(w) x 48(d) mm</p> <p>Max 110°C Max 10 Bar</p> <p>15TRVAWHCP Angled Valve</p>	 <p>White (10mm)</p> <p>Dimensions – 140(h) x 76(w) x 48(d) mm</p> <p>Max 110°C Max 10 Bar</p> <p>10TRVAWHCP Angled Valve</p>	 <p>One Piece Reducing Bullet</p> <p>Brass (15 x 10mm)</p> <p>Dimensions – 30(h) x 50(w) x 60(d) mm</p> <p>1510RED</p>	

INSTINCT²

The Ideal Instinct² Combi Boiler

Available in outputs of 24, 30 and 35 kW the Instinct² provides a cost effective heating solution for a range of domestic installations. Designed for a compact space, quick and easy to install and with a low lift weight, the Instinct² combi boiler is the perfect fit.

www.instinctproducts.co.uk

Pages
58-59



ideal
HEATING

5

YEAR WARRANTY*

Easy To
Install

Guarantees

1 Year on Designer Radiator Valves

Designer Radiator Valves

Contemporary / Traditional Radiator Valves



Best Seller

Contemporary, Polished Chrome (15mm – Pair)

Dimensions –
90.5(h) x 75(w) x 32(d) mm (Angled)
75(h) x 87.5(w) x 32(d) mm (Straight)
75(h) x 60(w) x 75(d) mm (Corner)

INST-AL025LC	Angled Valve
INST-AL024LC	Straight Valve
INST-AL029LC	Corner Valve



Square, Polished Chrome (15mm – Pair)

Dimensions –
82(h) x 76(w) x 30(d) mm (Angled)
64(h) x 95(w) x 30(d) mm (Straight)

INST-AL030LC	Angled Valve
INST-AL031LC	Straight Valve



Traditional, Polished Chrome (1/2" x 15mm – Pair)

Dimensions –
110(h) x 115(w) x 46(d) mm

INST-AL034LC	Angled Valve
--------------	--------------

Coloured Valves



Matt Black (1/2" x 15mm)

Dimensions –
83(h) x 75(w) x 30(d) mm (Angled)
78(h) x 75(w) x 30(d) mm (Straight)
73(h) x 70(w) x 70(d) mm (Corner)

INCNT003AP-ZMB	Angled Valve
INCNT003ST-ZMB	Straight Valve
INCNT023-MB	Corner Valve



Anthracite (1/2" x 15mm)

Dimensions –
83(h) x 75(w) x 30(d) mm (Angled)
78(h) x 75(w) x 30(d) mm (Straight)
73(h) x 70(w) x 70(d) mm (Corner)

INCNT003AP-ZAT	Angled Valve
INCNT003ST-ZAT	Straight Valve
INCNT023-AT	Corner Valve



Gloss White (1/2" x 15mm)

Dimensions –
83(h) x 75(w) x 30(d) mm (Angled)
78(h) x 75(w) x 30(d) mm (Straight)

INCNT003AP-GW	Angled Valve
INCNT003ST-GW	Straight Valve

Elements



15mm Dual Fuel Corner Radiator Valves (Pair)

Finish – Polished Chrome
Dimensions – 71.8(h) x 64.3(w) x 68.5/48.3(d) mm

INST-AL049LC

1/2" M & F Dual Fuel Elbow

Finish – Chrome

DFE12



Towel Rail Element (Inc. Tee Piece + 1/2" Plug)

Suitable for both dual-fuel and electric only
Maintains liquid temperature between 40-54°C

TRE150	150W	TRE600	600W
TRE250	250W	TRE800	800W
TRE400	400W		

Are you looking to replace or install a new radiator?

Pages 70-73

With a slim profile and smooth, white finish, Henrad Compact and Compact K3 radiators will blend into any room in the house, to provide guaranteed heating performance.

Multiple Sizes



Guarantees

1 Year on Manual Radiator Valves

Manual Radiator Valves

Angled Manual Radiator Valves



15 + 10mm Angled Manual Radiator Valve

Finish – Chrome / White
 Dimensions –
 31(h) x 72(w) x 70(d) mm (ER-15MMVAL)
 31(h) x 70(w) x 73(d) mm (ER-10MMVAL)

Max 85°C Max 20 Bar

ER-15MMVAL 15mm Angled Manual Valve
ER-10MMVAL 10mm Angled Manual Valve



15 + 10mm Angled Manual Radiator Valve (Drain Off)

Finish – Chrome / White
 Dimensions –
 31(h) x 75(w) x 88(d) mm (ER-15MMDOVAL)
 32(h) x 82(w) x 82(d) mm (ER-10MMDOVAL)

Max 85°C Max 20 Bar

ER-15MMDOVAL 15mm Angled Manual Valve (Drain Off)
ER-10MMDOVAL 10mm Angled Manual Valve (Drain Off)



15 + 10/8mm Angled Lockshield Manual Radiator Valve

Finish – Chrome / White
 Dimensions –
 35(h) x 78(w) x 75(d) mm (CEMMRV15)
 35(h) x 78(w) x 69(d) mm (CEMMRV10-8)

Max 85°C Max 20 Bar

CEMMRV15 15mm Angled Lockshield Manual Valve
CEMMRV10-8 10/8mm Angled Lockshield Manual Valve



15 + 10/8mm Angled Lockshield Manual Radiator Valve (Drain Off)

Finish – Chrome / White
 Dimensions –
 29(h) x 85(w) x 91(d) mm (CEMDRN15)
 29(h) x 85(w) x 91(d) mm (CEMDRN10-8)

Max 85°C Max 20 Bar

CEMDRN15 15mm Angled Lockshield Manual Valve (Drain Off)
CEMDRN10-8 10/8mm Angled Lockshield Manual Valve (Drain Off)

Straight Manual Radiator Valves



15mm Straight Manual Radiator Valve

Finish – Chrome / White
 Dimensions –
 33(h) x 63(w) x 89(d) mm

Max 85°C Max 20 Bar

ER-15MMSVAL 15mm Straight Manual Valve

Ancillaries



Radiator Drain Off Tail Piece

Finish – Chrome
 Dimensions –
 32(h) x 54(w) x 41(d) mm

Max 85°C Max 10 Bar

YU-JQAL213HC



Demountable 10mm Push Fit Elbow (Pair)

Finish – Chrome
 Dimensions –
 22(h) x 47(w) x 65(d) mm

Max 100°C Max 10 Bar

459004